

SLPO-12 Slim Line Pure Optical

The Slim Line Pure Optical turnstile system is a slimmer version of the Pure Optical turnstile. This is a 6 beam single direction, single detection lower level security turnstile.

The standard finish is Stainless Steel with a Corian top.



Method of Operation:

An access card or other credential is presented to the customer supplied access control reader mounted inside the casework. If entry is authorized, the top mounted indicator LEDs will light as a green arrow pointing in the direction authorized and a chime will sound indicating to the user that they may pass. Unauthorized access attempts and tailgaters are singled out by local visual/audible alarm.

Optical Detection:

Industrial duty infrared photoelectric beams (12) linked to Primary Input/output Board - 32-bit microprocessor with optional on board wireless LAN connectivity.

Throughput:

One person per second. (Subject to access control system outputs)

Tailgate Detection:

The system recognizes patterns of movement through the lane to differentiate between a person pushing or pulling an item and a person attempting to piggy back on a valid entry. Beam scanning algorithmic pattern detection allows valid users of the lane to be within ¼ inch.

Sound Card:

The Sound Card emits 4 different tones via an 8 ohm speaker to indicate lane status – i.e.; valid transaction, invalid card, unauthorized access attempt, or tailgate attempt. Digitally controlled, the Sound Card allows for volume adjustment on-board pedestal or via the optional touch screen controller.

Reader Integration:

Mounting for proximity card readers are located at both ends, immediately under the LED array. Bar Code readers, Swipe readers, biometric readers, or other access control systems can be integrated at both ends through coordination between access control dealer and Turnstiles.US.



SLPO-12 Slim Line Pure Optical

- Power:** 240w 24VDC 10A power supply is provided by manufacturer for each set of up to 4 lanes. A dedicated 120V 15A circuit should be provided at each location.
- Status Lights:** LED arrays are fitted into the pedestal tops, one for each direction, to visually assist the user when passing through the lane. Can also be front mounted if required.
- Bi-directional Card Stacking:** For increased throughput, the system is capable of receiving up to 50 authorized access card credits. If all of the access credits are not used or after 5 seconds of inactivity, the system will reset and secure the lane. Card stacking is active in both directions simultaneously.
- Warranty:** Three (3) year return-to-factory warranty on all electrical components.

TECHNICAL DATA

SLIM LINE PURE OPTICAL	TYPE	ADA	STANDARD
LANE WIDTH	Inches	36	28
PEDESTAL LENGTH WITH ROUNDED ENDS	Inches	12	12
PEDESTAL LENGTH WITH FLAT ENDS	Inches	12	12
PEDESTAL HEIGHT	Inches	38	38
PEDESTAL WIDTH	Inches	4	4

Dimensions are expressed in inches. The colors presented herein are merely illustrative. Turnstiles.US reserves the right to change product specifications without prior notice. Prices and specifications are subject to change without notice. Not responsible for typographical errors.