



NEMEH Multi-Biometric Face & Fingerprint Access Control Reader

NEMEH is the first access control reader to apply the most advanced SilkID fingerprint and face recognition technology together. NEMEH can operate in both bright light and total darkness.



Multi-biometric technology:

Identify or verify users by their face, fingerprint, proximity card or PIN/password... or any combination, all conveniently from a single device. Built-in infrared light source enables operation in dimly lit rooms.



Communication:

NEMEH installs easily on your network having both TCP/IP and RS485 serial ports. Its USB port allows for offline data backup and management when the network is unavailable.



Display/Audio:

Stunning 3-inch color TFT touch screen provides ease of use and rich user experience with intuitive and user friendly GUI. Includes both voice and visual prompts which indicate the acceptance or rejection of fingerprint, face, prox card or PIN/Password.



Capacity:

Supports one to many (1: N) matching for up to 2,000 faces and 4,000 fingerprint templates and 10,000 cards.



Options:

NEMEH can be configured with optional internal modules which read HID Prox, HID iclass or 13.56 MHz Mifare cards.



Access control:

Contact Relays for door locks, exit button, alarms & bell. Supports 50 time zones, 99 groups and 10 unlock combinations. Wiegand IN and OUT ports can be used to connect to access control panels.





For Software Developers:


Free SDK and development tools are available for developers/partners who wish to integrate NEMEH with any application which requires verifying people. Custom development is also available for OEM partners upon request.

Configuration

Dimensions







Specifications

Capacity

Faces: 2,000 (4,000 1:1) Fingerprints: 4,000 Cards: 10,000

Access Control Interface

Lock Relay Output Alarm Output/Auxiliary Input Exit Button/Door Sensor Doorbell Output

TCP/IP, RS485 (for slave reader) **USB Host**

Wiegand Input/Output

Hardware

SilkID Fingerprint Sensor 2.8 Inch TFT-LCD Touch Screen 125 kHz ZKAccess Card Reader Tamper Switch Alarm

Access Levels/Groups/Holidays DST/Bell Schedule Duress Mode (Password) Anti-Passback Record Query Custom Wallpaper & Screen Saver

Software Compatibility

EntraPASS Access Control Software


Additional Info

Working Temperature: 14° F to 122° F (-10° C to 50° C) Dimensions: 7.5 x 3.3 x 4 inches Package Includes: 12V 3A Power Supply


Power

Operating Voltage 12V DC Current Draw < 500mA

What's in the Box







Back Plate











Cables

Screws

Screwdriver

Diode