


## EntraBOX Guard Shack Through-the-Wall HVAC Unit



Smart

CONTROL W/APP

Quiet

UP TO 25% QUIETER

Cool

POWERFUL AIRFLOW



Integrated Wi-Fi control from your smartphone. Also compatible with Amazon Alexa or Google Home.

### Connect in minutes

It's easy with our simplified set up process

### Easily set your home, away, and night time preferences

Create a custom cooling schedule that fits your lifestyle

### You're in control anytime, anywhere

Power your unit on and off, change temperature, system mode, and adjust fan speeds no matter where you are

By maintaining even temperatures with centralized controls, you reduce wasted energy and lower utility and maintenance costs while extending the life of your equipment.

Google is a registered trademark of Google LLC.



## FEATURES

### Control Features

- Built-in Wi-Fi control on the go
- Smart home / voice command device compatibility (Amazon Alexa or Google Home)
- 24-hour timer
- Remote control

### QuietMaster Technology

- Solid-steel inner wall
- Advanced airflow design
- High density insulation and foam for sound absorption
- Aesthetically engineered to block indoor noise
- Counterweights for vibration dampening



### Comfort & Convenience

- 3 cooling and fan-only speeds
- Unique sleep setting
- Auto restart if power is interrupted
- 8-way air flow control
- Washable, antimicrobial air filter

### Earth Friendly

- ENERGY STAR® qualified models
- Money Saver® setting saves money by operating the fan only when cooling

### Reliable Construction

- Both the indoor and outdoor coils are corrosion protected for a longer life cycle



Easy-to-use remote control

### Installation Features

- Universal fit decorative trim ring
- Chassis designed to fit multiple existing sleeves from 24 1/2" to 27"




## QuietMaster technology

Building the quietest air conditioners begins with the design process and continues through the selection of superior components and materials.

It is shaped by skilled manufacturing and refined through on-going product testing in our engineering lab.

The result is a noticeably quieter cooling and heating experience, as much as 25% quieter than competitor's products.



## OPTIONAL ACCESSORIES

### USC SLEEVE

An existing or new sleeve is required for installation. The USC sleeve ships with the accessories needed for installation in new construction, or installation into an existing sleeve.

#### INCLUDED WITH USC SLEEVE

USC wall sleeve ships with weather panels (2) and grille. Sleeve is shown at right with:

1. Painted steel inner panel
2. Painted steel outer panel
3. Painted steel standard grille




USC sleeve



Inner weather panel



Outer weather panel



Standard grille

### OPTIONAL GRILLE

#### ARCHITECTURAL GRILLE-UXAA

Optional extruded brushed aluminum grille.



UXAA, optional architectural grille


#### IMPORTANT:

When installing into an existing sleeve, consult Installation Section of your Installation/Operation Manual to determine whether or not the grille needs to be replaced and/or a baffle adapter (included with chassis) should be used.

### SLEEVE/CHASSIS DIMENSIONS

Model	Depth			Minimum Extension Into Room	Minimum Extension Outside	Thru-the-wall Finished Hole			
	Height	Width	Depth			Height	Width	Max. Depth	
Uni-Fit®									
USC Sleeve	15 1/2"	25 7/8"	16 3/4"	20 1/2"	-	1/2"	15 3/4"	26 1/8"	16 1/4"
UCT, UET Chassis	14 1/2"	24 1/4"	-	20 5/16"	3 3/4"	-	-	-	-

NOTE: Chassis requires USC sleeve for new installations (sold and shipped separately).



**IMPORTANT:**


1" gap on sides and 1/2" gap at top allows installation into varying sleeve sizes.

The gap can be covered by the **decorative trim ring** that fits over the chassis front. Trim ring comes standard with chassis.

**IMPORTANT:**

**CHASSIS EXTENSION INTO THE ROOM**

UCT and UET chassis w/ front fully installed into USC sleeve extends into the room as shown at right **A**







SIDE VIEW

## SPECIFICATIONS

★ ENERGY STAR® models

Model	UPC	Cooling Btu	Heating Btu	Volts Rated	Cooling Amps	Cooling Watts	Heating Amps	Heating Watts	EER	CEER	Estimated		Moisture Removal Pints/Hr	Refrigerant	CFM	Sleeve	Net Weight Lbs	Ship Weight Lbs
											Yearly Energy Cost	Cost						
<b>UNI-FIT®</b>																		
<b>Cool Only</b>																		
★ UCT08A10A	724587436747	8000	—	115	6.9	755	—	—	10.7	10.6	\$69		0.8	R410A	265		64	78
★ UCT10A10A	724587436754	10000	—	115	8.3	940	—	—	10.7	10.6	\$85		1.25	R410A	247		74	86
★ UCT10A30B	724587440386	10000	—	230	4.5	940	—	—	10.7	10.6	\$85		1.25	R410A	265		74	86
★ UCT12A10A	724587436761	12000	—	115	10.1	1130	—	—	10.6	10.5	\$102		1.7	R410A	276		75	88
★ UCT12A30A	724587436778	12000	—	230	5.4	1130	—	—	10.6	10.5	\$102		1.7	R410A	265		75	88
UCT14A30B	724587440607	14000	—	230	7.2	1490	—	—	9.4	9.3	\$135		2.15	R410A	265		76	89
<b>Cool with Electric Heat</b>																		
UET08A11A	724587436792	8000	4200	115	7.2	810	12.5	1320	9.7	9.6	\$74		0.75	R410A	265		66	79
UET10A33A	724587436808	10000	10600	230	4.9	1030	15	3500	9.7	9.6	\$93		1.2	R410A	276		75	87
UET12A33A	724587436815	12000	10600	230	5.9	1230	15	3500	9.7	9.6	\$111		1.65	R410A	276		76	89
UET14A33A	724587436822	14000	10600	230	7.2	1490	15	3500	9.4	9.3	\$135		2.15	R410A	265		77	90

## PLUG FACE / CIRCUIT RATING / POWER CORD

Uni-Fit® Model Number	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
UCT08A10A, UCT10A10A, UCT12A10A	125V - 15A	5 - 15P	6	
UCT10A30B, UCT12A30A, UCT14A30B	250V - 15A	6 - 20P	6	
UET08A11A	125V - 15A	5 - 15P	4.75	
UET10A33A, UET12A33A, UET14A33A	250V - 20A	6 - 20P	4.75	



Electric Heat models utilize an electric heat strip to provide warm air quickly. They can be used for primary heating in moderate climates and as supplemental heating in colder climates. They are ideal for rooms that are always 'too cold in winter'. Your distributor can assist you in selecting the right unit for your particular climate and application.

Power cords are located on front left.

## CARTON DIMENSIONS

Model	Carton Dimensions Inches		
	Height	Width	Depth
<b>Uni-Fit®</b>			
USC Sleeve	17 7/8"	28"	19 1/4"
UCT, UET Chassis	16 3/8"	27 3/4"	26 5/8"

As an Energy Star® partner, the selected Energy Star® models meet the Energy Star® guidelines for energy efficiency. EER is the unit's Energy Efficiency Ratio; CEER is the unit's Combined Energy Efficiency Ratio.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.

Your energy costs will depend on your utility rates and use. The estimated energy cost is based on a electricity cost of \$.12 per kWh.

For more information, visit -[www.ftc.gov/energy](http://www.ftc.gov/energy).

ROOM AIR CONDITIONERS  
1830

