



FBL5000 SERIES

FBL5000 Single-Lane Flap Barrier Turnstile
FBL5011 Single-Lane Flap Barrier Turnstile
(w/ controller and RFID reader)
FBL5022 Single-Lane Flap Barrier Turnstile
(w/ controller and combination fingerprint & RFID reader)

The FBL5000 single-lane flap barrier turnstile is a compact and elegant costeffective entrance control system designed for high-traffic volume.

The FBL5000 is a single-lane flap barrier turnstile series designed for smooth and silent operation and draws very little power. It's made of stainless steel which makes FBL5000 highly durable.

FBL5000 acrylic barriers are normally held in a locked position, thus denying passage to the secured side. Upon FBL5000's reader (RFID and/or biometric) positively recognizing a user's valid access card or biometric credential, its barriers retract upward automatically, thus allowing users passage to the secured side.

During emergencies and power outages the barriers automatically retract upward, thereby ensuring users FAST unencumbered exit to safety.

FBL5000 provides both **security** and **convenience**, all in a very durable yet elegant compact design.

Built-in Reader Integration







- FBL5000 series can be preordered from the factory with an integrated RFID card or fingerprint reader (pictured on the left)... or any other biometric reader (i.e. face, finger-vein, palm-vein, etc). This greatly reduces installation time & expense.
- FBL5000 series and associated access control readers are all factory-tested prior to shipping.
- We provide true plug'n play turnstiles with the lowest possible total cost of ownership in the industry!



SPECIFICATIONS

Power Supply	AC 220V/110V, 50/60Hz
Operating Temperature	-18F to 140F degrees
Operating Humidity	5%-85%
Working Environment	Indoor/Outdoor (if sheltered)
Rated Power	120W
Lane Width	23.6 in
Traffic Throughput	42 passages per minute (RFID) / 35 PPM (fingerprint) / 11 PPM (Face)
Casework Material and Barrier Material	SUS304 stainless steel and acrylic
Visual Indicator	Yes. Access granted/denied and walking direction (entry or exit)
Audio Alarm	Yes
Control System	Input controlled by dry contact
Emergency Button Input	Yes
Infrared Sensor	Triggers alarm upon detection of unauthorized users and tailgaters
Turnstile Dimension	39.8 (h) x 11.8 (w) x 47.2 (d) inches
Turnstile Weight	278 lbs

Combine single-lane turnstile model FBL5000 with FBL5200 depending on lane requirement (FBL5000 includes TWO units):

