


Choose the functionality



Options

Functionality	MAIN RELAY	INDEPENDENT OUTPUTS	CONFIGURABLE OUTPUTS	DOOR POSITION INPUT	REQUEST TO EXIT INPUT	DOOR AJAR OUTPUTS	FORCED DOOR OUTPUTS	ALARM SHUNT	WIEGAND OUTPUTS	SECURED SERIES OUTPUTS
2000	●	●	●	●	●	●	●	●	●	●
212	●	●	●	●	●	●	●	●	●	●
232	●	●	●	●	●	●	●	●	●	●
242	●	●	●	●	●	●	●	●	●	●

Combine functionality with style

Style	2000	212	232	242
e	● 2000e			
eM	● 2000eM			
R		● 212R	● 232R	
SE		● 212SE	● 232SE	
i		● 212i	● 232i	
W		● 212w	● 232w	
iLM		● 212iLM	● 232iLM	
iLW		● 212iLW		● 242iLW
233			● 233	
FX			● 232FX	
prox.pad			● prox.pad	

iLW Style - Architectural Weather Resistant Backlit

Keypad | Styles

The iLW keypad has a chrome plated metal trim with hardened backlit keys. There are LED's shown through the face plate to indicate operation status and provide the user confirmation of PIN number entry. Designed for indoor or outdoor use, the iLW keypad mounts to any standard single-gang electrical back box and provides superior durability.

FEATURES

- Single-gang flush mount design
- Hardened backlit keys
- Heavy chrome plated trim ring
- Key press feedback via sounder and yellow LED
- Built-in assignable sounder
- Bi-color Red/Green LED indicates relay status
- Indoor/outdoor use
- Keypad Programmable
- Functionality mode: 212, 242

SPECIFICATIONS

- Operating Voltage: 10-30 VDC; 12-24 VAC auto-adjusting
- Dimensions: 3.47" x 5.14" x 0.71"
- Temperature tolerance: -20F to 130F



212iLW / 242iLW / SSW-iLW

FX Style - Harsh Environmental

Combining elegant looks and the durability of a solid-state keypad in a weather proof design, the FX style keypad can be utilized for most any application. Designed for outstanding performance in high traffic and harsh environments, the solid-state touch sensitive keypad will continue to operate in the worst of conditions. The electronics have been conformal coated in the manufacturing process accompanied with the keypad design, provide an unsurpassed level of application flexibility. There are two LED's to indicate operation status and provide the user with visual PIN entry confirmation.

FEATURES

- Heavy chrome plated trim ring
- Flush mount
- Fits single-gang electrical box
- Touch sensitive solid-state flat keys
- Bi-color LED to indicate operation
- Indoor/outdoor
- Internal sounder
- Functionality mode: 232

SPECIFICATIONS

- Dimensions: 3.44" x 5.16" x 0.71"
- Operating voltage: 12-24 VDC
- Temperature tolerance: -20F to 130F



232FX / SSW-FX