



## Cyclic Timer Relay

### Multi-functional Relay with Adjustable Timer

The cyclic ON first or OFF first timer offers 6 time ranges up to 10 sec/min/hr (ON Time) and 10 sec/min/hr (OFF time). The unit is panel/plug mounted. The cyclic timer is set using dials and is CE, UL, and RoHS certified. Additional 8-pin octal socket base needed for wire terminations.

#### Display Specifications

LED Indications	Power ON, Relay ON
-----------------	--------------------

#### Input Specifications

Accuracy	Setting: $\pm 5\%$ of F.S. Repeat: $\pm 0.5\%$ or 50 msec (F.S. = Full Scale)
----------	--

#### Output Specifications

Relay Contact	2 C/O DPDT
Contact Rating	5A @ 230V AC / 24V DC, resistive

#### Functional Specifications

Modes	Cyclic ON first or OFF first
Time Ranges	0 - 1sec / min / hr (ON Time) 0 - 10sec / min / hr (ON Time) 0 - 1sec / min / hr (OFF Time) 0 - 10sec / min / hr (OFF Time)
Resolution	0.1sec
Reset	On interruption of power; Reset time < 100msec

#### Auxiliary Supply Specifications

Supply Voltage	20 to 240V AC (50 / 60Hz) 12 to 240V DC
Power Consumption	3VA max

#### Environmental Specifications

Temperature	Operating: 0 to 50°C (32 to 122°F) Storage: -20 to 75°C (-4 to 167°F)
Humidity (non-condensing)	95% RH

#### Mechanical Specifications


Mounting	Plug / Panel Mount
Weight	80gms

#### Features:


- Cyclic Timer with Unequal ON & OFF Time
- 6 Time Ranges
- Universal Supply Voltage
- LED Indications : Power ON, Relay ON
- Compact Size 48 x 48mm

Certifications :

#### Dimensions



#### Terminal Connections



#### Timing Diagram

