quality modern competitive



## Full Height Turnstile **TX1500-UNO**

URNSTILES.US

ECURING THE U.S. and the GLOBE since 1989

www.TURNSTILES.us | patrick.mcallister@TURNSTILES.us | 303-670-1099

 Three arm, bi-directional turning mechanism.
Locks activated by optical sensors and electromagnets for low maintenance in any environment.

- Full round base reduces vibration, thereby increasing mechanical and electronic life spans.
- Manufactured with high strength square steel tubing. Welded arms and structure provides for the highest level of security and protection against vandalism and unauthorized intrusion.
- Electrolytic zinc, electrophoresis base paint and epoxy powder coating makes the TX ideal for indoor, outdoor and aggressive environments.
- Locking mechanism based on the unique and internationally proven technology of electromagnets.
- 6 Central arms in stainless steel for increased resistance and cleanliness on user touched surfaces.
- Special supports on the top cover ease the integration process with electronics and other security devices.
- ► Security key lock to access top cover.

DIMENSIONS


- Safety device on top cover avoids unwanted accidents during installation and maintenance.
- Supplied dismounted for easy installation and reduced transport costs.
- ▶ Pictograms also available as an optional item.




Option in mild steel with epoxy powder coating over heavy duty electrophoretic prime

RNSTILES

SECURING THE U.S. and the GLOBE since 1989



Please install leaving a free span of 12" over the turnstile in order to open the top cover.



Dimensions may vary up to 10mm.

Manufacturer reserves the right to modify any information contained in this catalog without prior notice.