

FUSION

FULL HEIGHT PRESTIGE TURNSTILE

**- 10 YEAR -
GUARANTEE**

INDUSTRY LEADER

- The FUSION is designed to be a high security and aesthetic access control solution
- Exported worldwide



APPLICATIONS

- Suited for applications requiring high volume access and high levels of security
- Used extensively in applications such as office reception areas, commercial buildings and universities

DESIGNED FOR

- Interior installations
- Harsh operating conditions

AVAILABLE CONFIGURATIONS

- 3 arm (120°)
- Single and double

SECURITY RATING

- 4/5

FEATURES OF THE FUSION FULL HEIGHT TURNSTILE

ROTALOK® ROTATION LOCKING MECHANISM

- Fitted to all Fusion Full Height turnstiles
- Ultra heavy-duty electromechanical rotation locking mechanism
- Bi-directional operation
- Designed by professional engineers
- Tried, tested and perfected over a period of over 20 years

RELIABLE TECHNOLOGY

- Self-centering rotation system - rotor returns to starting position after every rotation
- Anti-Trap® safety system - no mid-rotation locking or trapping in the event of a power failure
- Extra secure 60° anti-reverse system
- Programmable PLC logic with user diagnostic features
- Mechanical key override - clockwise and anti-clockwise directions (fail-secure)

DURABLE FEATURES

- Zinc plated for corrosion resistance
- Ultra quiet, buffered solenoids and pawls
- Solenoids rated for 100% duty cycle
- Case hardened locking disk and pawls - eliminating any wear
- Factory settings need no further adjustment
- No routine maintenance whatsoever, ever

RELATED PRODUCTS



TRITON CURVED



TRITON OCTAGONAL

TECHNICAL SPECIFICATIONS


POWER	220 Volt AC (110 Volt AC on request)
FREQUENCY	50Hz / 60Hz
POWER CONSUMPTION	50W
SOLENOID VOLTAGE	24 Volt DC (12 Volt DC on request)
LOGIC VOLTAGE	24 Volt DC
DIMENSIONS	Single turnstile 1 400mm wide x 2 240mm high Double turnstile 2 180mm wide x 2 240mm high
ROTOR DIAMETER	1 250mm
ROTOR WING CONFIGURATION	3 wing (120°)
FORM	Octagonal
ROTOR	Powder coated mild steel / brushed stainless steel
FRAME GLASS INFILL	6mm toughened glass
PUSH HANDLES	Stainless steel
LIGHTING	Low-voltage downlighters
DESIGN	Modular bolt-together design for ease of transport and installation. Components can pass through a standard door. Can be packed in broken-down form either onto a pallet or into a crate for transport
SYSTEMS INTEGRATION	<ul style="list-style-type: none"> Integrates with all access control and time and attendance systems Unlocking for entry / exit rotation controlled through normally open dry contact Transaction / rotation complete output Integral wireways with draw wires in place - no exposed wires

MANUFACTURING OPTIONS


ROTATION OPTIONS	<ul style="list-style-type: none"> Electrically controlled bi-directional rotation (factory standard) Mechanically controlled uni-directional rotation by means of key override Free rotation
LOCKING OPTIONS	<ul style="list-style-type: none"> Fail-secure auto-lock on power failure (factory standard) Fail-safe auto-unlock on power failure Each direction of rotation configurable for either fail-secure or fail-safe operation
FIRE ALARM OPTIONS	Free rotation when triggered indefinitely (logic programmed for direction or rotation on request)
POWER OPTIONS	Battery backup with two 12 volt 7Ah batteries connected in series <ul style="list-style-type: none"> Up to 1 000 transactions in fail-safe mode Up to 60 minutes operation in fail-safe mode
ACCESSORY OPTIONS	<ul style="list-style-type: none"> Card / proximity reader mounting brackets Biometric / fingerprint reader mounting brackets Single / double pushbutton in plastic housing LED red cross and green arrow indicator light
FRAME & ROTOR FINISH OPTIONS	<ul style="list-style-type: none"> Mild steel with UV resistant polyester exterior powder coat finish (charcoal blue hammertone) ■ 304 grade brushed stainless steel 316 grade brushed stainless steel ▲ <p>▲ suitable for highly corrosive environments (details available on request) ■ other colours available on request</p>

FUSION RANGE

SINGLE




ELEVATION




PLAN

DOUBLE



ELEVATION



PLAN